

HDP

High Performance Parking Garage Doors

SPRINGLESS LOW HEADROOM



TNR® offers a high performance, high speed rubber roll-up door ideal for parking garage applications:

DOOR IMPACT CONCERNS
from fast moving vehicle traffic

LOW MAINTENANCE COSTS
easier and faster to repair, less downtime

HIGH TRAFFIC
continual vehicle flow with peak periods

LOW HEADROOM
suitable for underground parking entrances



***Tough 'n' Ready
For Your Challenging
Environments***

HDP Heavy Duty Parking

TNR® combines rugged durability with a high performance drive system for a superior parking garage door solution.

Outstanding reliability, minimal downtime and fast operation are essential requirements of parking garage door applications. Property and Maintenance Managers recognize the value of TNR Doors proven indestructibility and endurance combined with high speed performance. The Heavy Duty Parking garage door is ideal for: condos, office complexes, hotels, underground parking garages, airports.

TNR® Mechanical Features

- 1/4" Black SBR rubber with polyester core weave. Flexible and resistant to abusive environments and impacts in temperatures from -40°F to +180°F.
- Patented NEWGEN® guide and Curtain Lok™ system. Reliable and consistent door operation and impact release performance. No guide gap maintenance required.
- Impactable: After impact, the door is up and running in minutes.
- Knock-away double angle steel bottom bar with rubber loop and reversing edge.
- Sleek profile with easy installation, reduced clearances & minimal maintenance.
- No hinges, cables, pulleys or springs allowing for minimum 18" low headroom installation.
- Self-supporting steel frame.
- Frame mounted thru-beam photoelectric sensor.
- Options: colors, windows, hoods, reversing edge, traveling windbar and MSHA-rated self-extinguishing curtains.

TNR® Drive Features

- High Efficiency Helical Gear Head (HG) Operator with multi-function capacity PLC.
- Variable door speed, depending on door size.
- Options: access controls and specialty functions.

Standard HDP Door Features
Door Size —Maximum 25' wide x 10' high
Opening Speed —Up to 30 inches per second
Clearance —Minimum 18 inches of headroom
Springless Design —With optional inertia brake
Curtain Type —1/4" Black SBR rubber with polyester core weave
Reversing Edge —Pressure sensitive air-wave edge
Control Panel —PLC and Inverter Drive soft start, soft stop
Activation —Remote controls, pull cords, loop detectors
Self Supporting Steel Frame —Steel Mounting Angle
Warranty —Limited lifetime warranty on curtain and NEWGEN® Guide. Five years or 1,000,000 cycles on operator with frequency drive. Two years on all other parts and workmanship.

NEWGEN® Guide and Curtain Lok™ system

